

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Proposed Amendment) A method of wireless communications, comprising:
establishing a packet data session from a wireless communications device to support a network connection to a packet-switched network;
transmitting a registration request, from the wireless communications device, over the packet data session to a voice message server using a session key to enable the wireless communications device to receive a notification from the voice message server of an incoming call from a circuit-switched network, the registration request including connection information identifying the wireless communications device; and
receiving the notification, in the wireless communications device identified by the connection information, from the voice message server while the ~~network connection to the packet-switched network~~ packet data session is active.
2. (Canceled).
3. (Canceled).
4. (Canceled
5. (Previously Presented) The method of claim 1 wherein the registration comprises communication from the wireless communications device with the voice message server over a transport control protocol session.
6. (Original) The method of claim 1 further comprising terminating the packet data session in response to the notification of the incoming call, and accepting the incoming call from the circuit-switched network.

7. (Previously Presented) The method of claim 6 wherein the acceptance of the incoming call comprises establishing a connection with a mobile switching center to support the incoming call.

8. (Canceled).

9. (Currently Amended) ~~The method of claim 1 further comprising~~

A method of wireless communications, comprising:

establishing a packet data session from a wireless communications device to support a network connection to a packet-switched network;

transmitting a registration request, from the wireless communications device, over the packet data session to a voice message server to enable the wireless communications device to receive a notification from the voice message server of an incoming call from a circuit-switched network, the registration request including connection information identifying the wireless communications device;

receiving the notification, in the wireless communications device identified by the connection information, from the voice message server while the packet data session is active;
and

sending a reply from the wireless communications device to the voice message server in response to the notification.

10. (Original) The method of claim 9 wherein the reply is sent over the packet data session.

11. (Previously Presented) The method of claim 1 further comprising terminating the packet data session in response to the notification, and establishing a connection with a mobile switching center to support the incoming call.

12. (Currently Amended) A wireless communications device, comprising:

a processor configured to establish a packet data session to support a network connection to a packet-switched network, transmit a registration request, from the wireless communications

device, over the packet data session to a voice message server using a session key to enable the wireless communications device to receive a notification from the voice message server of an incoming call from a circuit-switched network, the registration request including connection information identifying the wireless communications device, and receive the notification, in the wireless communications device identified by the connection information, from the voice message server while the packet data session ~~network connection to the packet-switched network~~ is active.

13. (Canceled).

14. (Canceled).

15. (Canceled)

16. (Previously Presented) The wireless communications device of claim 12 wherein the processor is further configured to register with the voice message server over a transport control protocol session.

17. (Original) The wireless communications device of claim 12 wherein the processor is further configured to terminate the packet data session in response to the notification, and accept the incoming call from the circuit-switched network.

18. (Original) The wireless communications device of claim 17 wherein the processor is further configured to accept the incoming call by establishing a connection with a mobile switching center to support the incoming call.

19. (Canceled).

20. (Currently Amended) ~~The wireless communications device of claim 12~~
A wireless communications device, comprising:

a processor configured to establish a packet data session to support a network connection to a packet-switched network, transmit a registration request, from the wireless communications device, over the packet data session to a voice message server to enable the wireless communications device to receive a notification from the voice message server of an incoming call from a circuit-switched network, the registration request including connection information identifying the wireless communications device, and receive the notification, in the wireless communications device identified by the connection information, from the voice message server while the packet data session is active,

wherein the processor is further configured to send a reply to the voice message server in response to the notification.

21. (Original) The wireless communications device of claim 20 wherein the processor is further configured to send the reply over the packet data session.

22. (Previously Presented) The wireless communications device of claim 21 wherein the processor is further configured to terminate the packet data session in response to the notification, and establish a connection with a mobile switching center to support the incoming call.

23. (Currently Amended) A wireless communications device, comprising:

means for establishing a packet data session to support a network connection to a packet-switched network;

means for transmitting a registration request, from the wireless communications device, over the packet data session to a voice message server using a session key to enable the wireless communications device to receive a notification from the voice message server of an incoming call from a circuit-switched network, the registration request including connection information identifying the wireless communications device; and

means for receiving the notification, in the wireless communications device identified by the connection information, while the packet data session ~~network connection to the packet-switched network~~ is active.

24. (Currently Amended) A method of wireless communications, comprising:
establishing a packet data session between a wireless communications device and a packet data serving node to support a network connection with a packet-switched network;
transmitting a registration request, from the wireless communications device, over the packet data session to a voice message server using a session key to enable the wireless communications device to receive a notification from the voice message server of an incoming call from a circuit-switched network, the registration request including connection information identifying the wireless communications device; and
routing the notification of an incoming circuit-switched call from the voice message server to the wireless communications device identified by the connection information while the packet data session ~~network connection to the packet-switched network~~ is active.
25. (Original) The method of claim 24 wherein the notification is sent over the packet data session between the wireless communications device and the packet data serving node.
26. (Canceled).
27. (Original) The method of claim 24 further comprising terminating the packet data session between the wireless communications device and the packet data serving node in response to the notification, and establishing a connection between the wireless communications device and a mobile switching center to support the incoming call.
28. (Currently Amended) ~~The method of claim 24 further comprising~~
A method of wireless communications, comprising:
establishing a packet data session between a wireless communications device and a packet data serving node to support a network connection with a packet-switched network;
transmitting a registration request, from the wireless communications device, over the packet data session to a voice message server to enable the wireless communications device to receive a notification from the voice message server of an incoming call from a circuit-switched network, the registration request including connection information identifying the wireless communications device;

routing the notification of an incoming circuit-switched call from the voice message server to the wireless communications device identified by the connection information while the packet data session is active;

receiving the incoming call at a mobile switching center while the network connection is active;[[,]]

routing a signal from the mobile switching center to the voice message server indicating that the wireless communications device is unavailable, the receipt of the signal at the voice message server prompting the routing of the notification from the voice message server to the wireless communications device;~~the method further comprising~~

routing a reply from the wireless communications device to the voice message server[[,]]
; and

signaling the mobile switching center from the voice message server to deliver the incoming call to the wireless communications device in response to the reply.

29. (Currently Amended) A method of communications, comprising:

operating a wireless communications device in a serving network, the wireless communications device being assigned to a home network different from the serving network;

establishing a packet data session between the wireless communications device and a packet data serving node in the serving network to support a network connection with a packet-switched network:

transmitting a registration request, from the wireless communications device, over the packet data session to a voice message server using a session key to enable the wireless communications device to receive a notification from the voice message server of an incoming call from a circuit-switched network, the registration request including connection information identifying the wireless communications device; and

routing the notification of an incoming circuit-switched call from the voice message server in the home network to the wireless communications device identified by the connection information over the packet data session while the network connection is active.

30. (Canceled).

31. (Canceled).

32. (Original) The method of claim 29 further comprising terminating the packet data session between the wireless communications device and the packet data serving node in the serving network in response to the notification, and establishing a connection between the wireless communications device and a mobile switching center in the serving network to support the incoming call.

33. (Currently Amended) ~~The method of claim 29 further comprising~~

A method of communications, comprising:
operating a wireless communications device in a serving network, the wireless
communications device being assigned to a home network different from the serving network;
establishing a packet data session between the wireless communications device and a
packet data serving node in the serving network to support a network connection with a packet-
switched network;

transmitting a registration request, from the wireless communications device, over the
packet data session to a voice message server using a session key to enable the wireless
communications device to receive a notification from the voice message server of an incoming
call from a circuit-switched network, the registration request including connection information
identifying the wireless communications device;

routing the notification of an incoming circuit-switched call from the voice message
server in the home network to the wireless communications device identified by the connection
information over the packet data session while the network connection is active;

receiving the incoming call at a mobile switching center in the home network while the network connection is active; ~~[,]~~

routing a signal from the mobile switching center in the home network to the voice message server in the home network indicating that the wireless communications device is unavailable, the receipt of the signal at the voice message server in the home network prompting the routing of the notification of the incoming call from the voice message server in the home network to the wireless communications device; ~~the method further comprising~~

routing a reply from the wireless communications device to the voice message server in the home network; [[,]] and

signaling the mobile switching center in the serving network from the voice message server in the serving network to deliver the incoming call to the wireless communications device in response to the reply.

34. (Currently Amended) A non-transitory storage medium having instructions thereon, the instructions comprising:

code for establishing a packet data session from a wireless communications device to support a network connection to a packet-switched network;

code for transmitting a registration request, from the wireless communications device, over the packet data session to a voice message server using a session key to register the wireless communications device to receive a notification of an incoming call from a circuit-switched network; and

code for receiving the notification, in the wireless communications device identified by the connection information, from the voice message server while the packet data session ~~network connection to the packet-switched network~~ is active.

35. (Previously Presented) A method of wireless communications, comprising:

establishing a packet data session between a wireless communications device and a packet data serving node to support a network connection with a packet-switched network;

routing a notification of an incoming circuit-switched call from a voice message server to the wireless communications device while the network connection is active; and

receiving the incoming call at a mobile switching center while the network connection is active, routing a signal from the mobile switching center to the voice message server indicating that the wireless communications device is unavailable, the receipt of the signal at the voice message server prompting the routing of the notification from the voice message server to the wireless communications device, the method further comprising routing a reply from the wireless communications device to the voice message server, and signaling the mobile switching center from the voice message server to deliver the incoming call to the wireless communications device in response to the reply.

36. (Previously Presented) A method of communications, comprising:

operating a wireless communications device in a serving network, the wireless communications device being assigned to a home network different from the serving network;

establishing a packet data session between the wireless communications device and a packet data serving node in the serving network to support a network connection with a packet-switched network;

routing a notification of an incoming circuit-switched call from a voice message server in the home network to the wireless communications device while the network connection is active; and

receiving the incoming call at a mobile switching center in the home network while the network connection is active, routing a signal from the mobile switching center in the home network to the voice message server in the home network indicating that the wireless communications device is unavailable, the receipt of the signal at the voice message server in the home network prompting the routing of the notification of the incoming call from the voice message server in the home network to the wireless communications device, the method further comprising routing a reply from the wireless communications device to the voice message server in the home network, and signaling the mobile switching center in the serving network from the voice message server in the serving network to deliver the incoming call to the wireless communications device in response to the reply.

37. (Previously Presented) The method of claim 1, wherein the connection information includes an IP address assigned to the wireless communications device.

38. (Previously Presented) The wireless communication device of claim 12, wherein the connection information includes an IP address assigned to the wireless communications device.

39. (Previously Presented) The method of claim 24, wherein the connection information includes an IP address assigned to the wireless communications device.